



SAFETY DATA SHEET

Page 1 of 5

OUTRAGEOUS EXTREME DESIGNER SOLID PEARL LIGHT GOLD

Revision 0
Revision date 24-Jun-2008

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

| | |
|-----------------------------------|--|
| Product name | OUTRAGEOUS EXTREME DESIGNER SOLID PEARL LIGHT GOLD |
| Company | Pro-Spray Automotive Finishes Limited Whitehall Industrial Estate Cambridge Road Croxtton St Neots PE19 6SS Colour@pro-spray.co.uk |
| Telephone | +44 (0) 1480 880035 (US) 1.330.830.6000 |
| Fax | +44 (0) 1480 880108 |
| Emergency telephone number | Chemtrec 1-800-424-9300 |
| Product code | DP-6036 |

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

| | Conc. | CAS | EINECS | Symbols/Risk phrases |
|--|----------|------------|-----------|---|
| n-Butyl acetate (Butyl acetate) | 40 - 50% | 123-86-4 | 204-658-1 | R10 R66 R67 |
| 2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate) | 10 - 20% | 108-65-6 | 203-603-9 | R10 Xi; R36 |
| Mica (Mica respirable) | 1 - 10% | 12001-26-2 | | |
| Iron Oxide (Rouge respirable) | 0 - 0.5% | 1309-37-1 | 215-168-2 | |
| Di-isobutyl ketone (2,6-Dimethylheptan-4-one) | 0 - 0.5% | 108-83-8 | 203-620-1 | R10 Xi; R37 |
| Xylene (Xylene, o-,m-,p-or mixed isomers) | 1 - 10% | 1330-20-7 | 215-535-7 | R10 Xn; R20/21 Xi; R38 |
| Butan-1-ol | 1 - 10% | 71-36-3 | 200-751-6 | R10 Xn; R22 Xi; R37/38-41 R67 |
| Benzyl butyl phthalate | 0.5 - 1% | 85-68-7 | 201-622-7 | Repr Cat 2; R61 Repr Cat 3; R62 N; R50/53 |
| Ethylbenzene | 0.5 - 1% | 100-41-4 | 202-849-4 | F; R11 Xn; R20 |
| Methanol | 0 - 0.5% | 67-56-1 | 200-659-6 | F; R11 T; R23/24/25-39/23/24/25 |
| Ethanol | 0 - 0.5% | 64-17-5 | 200-578-6 | F; R11 |
| 1-Methoxy-2-propanol (1-Methoxypropan-2-ol) | 0 - 0.5% | 107-98-2 | 203-539-1 | R10 |
| Low boiling point naphtha - unspecified - solvent naphtha (petroleum), light arom | 1 - 10% | 64742-95-6 | 265-199-0 | Xi; R37-66 N; R51/53 R10-67 |
| 1,3,5-Trimethylbenzene | 0 - 0.5% | 108-67-8 | 203-604-4 | R10 Xi; R37 N; R51/53 |
| Cumene | 0 - 0.5% | 98-82-8 | 202-704-5 | R10 Xn; R65 Xi; R37 N; R51/53 |
| 1,2,4-Trimethylbenzene | 0.5 - 1% | 95-63-6 | 202-436-9 | R10 Xn; R20 Xi; R36/37/38 N; R51/53 |

Print date

24-Jun-2008

OUTRAGEOUS EXTREME DESIGNER SOLID PEARL LIGHT GOLD

Revision 0

Revision date 24-Jun-2008

3. HAZARDS IDENTIFICATION

Main hazards Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. May cause harm to the unborn child. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.

Ingestion Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.

General information In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

5. FIRE FIGHTING MEASURES

Extinguishing media Alcohol resistant foam. Carbon dioxide (CO2) Dry chemical. Do NOT use water jet.

Fire hazards Burning produces irritating, toxic and obnoxious fumes. Fire will produce dense black smoke.

Protective equipment Self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.

Environmental precautions Do not allow product to enter drains. Prevent further spillage if safe.

Clean up methods Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

OUTRAGEOUS EXTREME DESIGNER SOLID PEARL LIGHT GOLD

Revision 0
Revision date 24-Jun-2008

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

| | | |
|---|--|--|
| n-Butyl acetate (Butyl acetate) | WEL 8-hr limit ppm: 150 WEL 15 min limit ppm: 200 | WEL 8-hr limit mg/m3: 724 WEL 15 min limit mg/m3: 966 |
| 2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate) | WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 | WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548 |
| Mica (Mica respirable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 0.8 WEL 15 min limit mg/m3: - |
| Mica (Mica respirable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 0.8 WEL 15 min limit mg/m3: - |
| Mica (Mica total inhalable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - |
| Iron Oxide (Rouge respirable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 4 WEL 15 min limit mg/m3: - |
| Iron Oxide (Rouge respirable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 4 WEL 15 min limit mg/m3: - |
| Iron Oxide (Rouge total inhalable) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 10 WEL 15 min limit mg/m3: - |
| Iron Oxide (Iron oxide, fume (as Fe)) | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 5 WEL 15 min limit mg/m3: 10 |
| Di-isobutyl ketone (2,6-Dimethylheptan-4-one) | WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 148 WEL 15 min limit mg/m3: - |
| Xylene (Xylene, o-,m-,p-or mixed isomers) | WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100 | WEL 8-hr limit mg/m3: 220 WEL 15 min limit mg/m3: 441 |
| Butan-1-ol | WEL 8-hr limit ppm: - WEL 15 min limit ppm: 50 | WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: 154 |
| Benzyl butyl phthalate | WEL 8-hr limit ppm: - WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 5 WEL 15 min limit mg/m3: 7.9 |
| Ethylbenzene | WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 125 | WEL 8-hr limit mg/m3: 441 WEL 15 min limit mg/m3: 552 |
| Methanol | WEL 8-hr limit ppm: 200 WEL 15 min limit ppm: 250 | WEL 8-hr limit mg/m3: 266 WEL 15 min limit mg/m3: 333 |
| Ethanol | WEL 8-hr limit ppm: 1000 WEL 15 min limit ppm: - | WEL 8-hr limit mg/m3: 1920 WEL 15 min limit mg/m3: - |
| 1-Methoxy-2-propanol (1-Methoxypropan-2-ol) | WEL 8-hr limit ppm: 100 WEL 15 min limit ppm: 150 | WEL 8-hr limit mg/m3: 375 WEL 15 min limit mg/m3: 560 |
| Cumene | WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50 | WEL 8-hr limit mg/m3: 125 WEL 15 min limit mg/m3: 250 |

Engineering measures

Ensure adequate ventilation of the working area.

Respiratory protection

Wear suitable respiratory equipment when necessary.

Hand protection

Chemical resistant gloves (PVC)

Eye protection

Approved safety goggles.

OUTRAGEOUS EXTREME DESIGNER SOLID PEARL LIGHT GOLDRevision 0
Revision date 24-Jun-2008

Protective equipment Wear chemical protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|----------------------------------|----------------------|
| Description | Liquid. |
| Flash point | 23~<32°C |
| Water solubility | immiscible in water. |
| VOC (Volatile organic compounds) | 740 g/l |

10. STABILITY AND REACTIVITY

| | |
|----------------------------------|---|
| Stability | Stable under normal conditions. |
| Conditions to avoid | Heat, sparks and open flames. |
| Materials to avoid | Oxidising agents. Acids. Alkaline solution. |
| Hazardous decomposition products | Carbon oxides. Nitrogen oxides. |

11. TOXICOLOGICAL INFORMATION

| | |
|--------------------------------|--|
| Acute toxicity | No data is available on this product. Exposure above the recommended occupational exposure limit (OEL) may cause adverse health effects. Inhalation is irritating to the respiratory tract and may cause damage to the central nervous system. |
| Corrosivity | May cause irritation to eyes and respiratory system. |
| Repeated or prolonged exposure | May cause dermatitis. |

12. ECOLOGICAL INFORMATION

| | |
|-------------|---------------------------------------|
| Ecotoxicity | No data is available on this product. |
|-------------|---------------------------------------|

13. DISPOSAL CONSIDERATIONS

| | |
|-----------------------|--|
| General information | Dispose of in compliance with all local and national regulations. |
| Disposal of packaging | Containers must be recycled in compliance with national legislation and environmental regulations. |

14. TRANSPORT INFORMATION**ADR/RID**

| | |
|----------------------|--------------------------|
| UN 1263 | Packing group III |
| Class 3 | Hazard ID 33 |
| Proper Shipping Name | PAINT RELATED MATERIAL . |

IMDG

| | |
|----------|--------------------|
| UN 1263 | Packing group III |
| Class 3 | Marine pollutant . |
| EmS Code | F-E S-E |

IATA

| | |
|-------------------------------------|------------------------|
| UN 1263 | Packing group III |
| Class 3 | Subsidiary risk - |
| Packing Instruction 310 (Cargo) | Maximum quantity 220 L |
| Packing Instruction 309 (Passenger) | Maximum quantity 60 L |

OUTRAGEOUS EXTREME DESIGNER SOLID PEARL LIGHT GOLD


Revision

0

Revision date

24-Jun-2008

15. REGULATORY INFORMATION

| | |
|-----------------------|--|
| Labelling | The product is classified in accordance with 67/548/EEC. |
| Symbols | T - Toxic  |
| Risk phrases | R36 - Irritating to eyes. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R61 - May cause harm to the unborn child. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness. |
| Safety phrases | S53 - Avoid exposure - obtain special instructions before use. |

16. OTHER INFORMATION

| | |
|--|--|
| Text of risk phrases in Section 2 | R10 - Flammable. R11 - Highly flammable. R20 - Harmful by inhalation. R20/21 - Harmful by inhalation and in contact with skin. R22 - Harmful if swallowed. R23/24/25 - Toxic by inhalation, in contact with skin and if swallowed. R36 - Irritating to eyes. R36/37/38 - Irritating to eyes, respiratory system and skin. R37 - Irritating to respiratory system. R37/38 - Irritating to respiratory system and skin. R38 - Irritating to skin. R39/23/24/25 - Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed. R41 - Risk of serious damage to eyes. R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R61 - May cause harm to the unborn child. R62 - Possible risk of impaired fertility. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness. |
| Further information | The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. |
| Maximum content of VOC | 740 g/l |