



## SAFETY DATA SHEET

Page 1 of 4

# OUTRAGEOUS EXTREME 2 - 1 MS SLOW ACTIVATOR

Revision 2  
Revision date 24-Jun-2008

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

**Product name** OUTRAGEOUS EXTREME 2 - 1 MS SLOW ACTIVATOR

**Company** Pro-Spray Automotive Finishes Limited  
Whitehall Industrial Estate  
Cambridge Road  
Croxtton  
St Neots  
PE19 6SS  
Colour@pro-spray.co.uk

**Telephone** +44 (0) 1480 880035 (US) 1.330.830.6000

**Fax** +44 (0) 1480 880108

**Emergency telephone number** Chemtrec 1-800-424-9300

**Product code** NA-6170

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

#### Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Xylene (Xylene, o-,m-,p-or mixed isomers)	1-10%	1330-20-7	215-535-7	R10 Xn; R20/21 Xi; R38
1,3,5-Trimethylbenzene	1-10%	108-67-8	203-604-4	R10 Xi; R37 N; R51/53
Cumene	0.5-1%	98-82-8	202-704-5	R10 Xn; R65 Xi; R37 N; R51/53
1,2,4-Trimethylbenzene	1-10%	95-63-6	202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53
Low boiling point naphtha - unspecified - solvent naphtha (petroleum), light arom	10-20%	64742-95-6	265-199-0	Xi; R37-66 N; R51/53 R10-67
Butylglycol acetate (2-Butoxyethyl acetate)	10-20%	112-07-2	203-933-3	Xn; R20/21

### 3. HAZARDS IDENTIFICATION

**Main hazards** May cause sensitisation by skin contact. Flammable Harmful by inhalation and in contact with skin. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

# OUTRAGEOUS EXTREME 2 - 1 MS SLOW ACTIVATOR

Revision 2  
Revision date 24-Jun-2008

## 4. FIRST AID MEASURES

<b>Skin contact</b>	May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
<b>Eye contact</b>	May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
<b>Inhalation</b>	Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
<b>Ingestion</b>	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist.
<b>General information</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media</b>	Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ) Dry chemical. Do NOT use water jet.
<b>Fire hazards</b>	Burning produces irritating, toxic and obnoxious fumes. Fire will produce dense black smoke.
<b>Protective equipment</b>	Self-contained breathing apparatus.

## 6. ACCIDENTAL RELEASE MEASURES

<b>Personal precautions</b>	Ensure adequate ventilation of the working area. Evacuate personnel to a safe area. Eliminate all sources of ignition. Wear suitable protective equipment.
<b>Environmental precautions</b>	Do not allow product to enter drains. Prevent further spillage if safe.
<b>Clean up methods</b>	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## 7. HANDLING AND STORAGE

<b>Handling</b>	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Use explosion proof equipment. Keep away from sources of ignition - No smoking.
<b>Storage</b>	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure limits

Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50	WEL 8-hr limit mg/m <sup>3</sup> : 220
	WEL 15 min limit ppm: 100	WEL 15 min limit mg/m <sup>3</sup> : 441
Cumene	WEL 8-hr limit ppm: 25	WEL 8-hr limit mg/m <sup>3</sup> : 125
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m <sup>3</sup> : 250
Butylglycol acetate (2-Butoxyethyl acetate)	WEL 8-hr limit ppm: 20	WEL 8-hr limit mg/m <sup>3</sup> : -
	WEL 15 min limit ppm: 50	WEL 15 min limit mg/m <sup>3</sup> : -

<b>Engineering measures</b>	Ensure adequate ventilation of the working area.
<b>Respiratory protection</b>	Wear suitable respiratory equipment when necessary.
<b>Hand protection</b>	Chemical resistant gloves (PVC)
<b>Eye protection</b>	Approved safety goggles.
<b>Protective equipment</b>	Wear chemical protective clothing.

# OUTRAGEOUS EXTREME 2 - 1 MS SLOW ACTIVATOR

Revision 2  
Revision date 24-Jun-2008

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Flash point	23~<32°C
Water solubility	immiscible in water.
VOC (Volatile organic compounds)	559 g/l

## 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
Conditions to avoid	Heat, sparks and open flames.
Materials to avoid	Oxidising agents. Acids. Alkaline solution.
Hazardous decomposition products	Carbon oxides. Nitrogen oxides.

## 11. TOXICOLOGICAL INFORMATION

Acute toxicity	No data is available on this product. Exposure above the recommended occupational exposure limit (OEL) may cause adverse health effects. Inhalation is irritating to the respiratory tract and may cause damage to the central nervous system.
Corrosivity	May cause irritation to eyes and respiratory system.
Repeated or prolonged exposure	May cause dermatitis.

## 12. ECOLOGICAL INFORMATION

Ecotoxicity	No data is available on this product.
-------------	---------------------------------------

## 13. DISPOSAL CONSIDERATIONS

General information	Dispose of in compliance with all local and national regulations.
Disposal of packaging	Containers must be recycled in compliance with national legislation and environmental regulations.

## 14. TRANSPORT INFORMATION

### ADR/RID

UN 1263	Packing group III
Class 3	Hazard ID 33
Proper Shipping Name PAINT .	

### IMDG

UN 1263	Packing group III
Class 3	Marine pollutant .
EmS Code F-E S-E	


### IATA

UN 1263	Packing group III
Class 3	Subsidiary risk -
Packing Instruction 310 (Cargo)	Maximum quantity 220 L
Packing Instruction 309 (Passenger)	Maximum quantity 60 L

# OUTRAGEOUS EXTREME 2 - 1 MS SLOW ACTIVATOR

Revision 2  
Revision date 24-Jun-2008

## 15. REGULATORY INFORMATION

<b>Labelling</b>	The product is classified in accordance with 67/548/EEC.
<b>Symbols</b>	Xn - Harmful 
<b>Risk phrases</b>	R43 - May cause sensitisation by skin contact. R10 - Flammable. R20/21 - Harmful by inhalation and in contact with skin. R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<b>Safety phrases</b>	S36/37 - Wear suitable protective clothing and gloves.

## 16. OTHER INFORMATION

<b>Text of risk phrases in Section 2</b>	R10 - Flammable. R20 - Harmful by inhalation. R20/21 - Harmful by inhalation and in contact with skin. R36/37/38 - Irritating to eyes, respiratory system and skin. R37 - Irritating to respiratory system. R38 - Irritating to skin. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.
<b>Further information</b>	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.
<b>Revision</b>	This document differs from the previous version in the following areas: 9 - flash point. 9 - vOC (Volatile organic compounds).
<b>Maximum content of VOC</b>	559 g/l