



SAFETY DATA SHEET

Page 1 of 4

OUTRAGEOUS EXTREME CLEARCOAT EDGE BLENDER/ FADE OUT

Revision 3
Revision date 24-Jun-2008

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name OUTRAGEOUS EXTREME CLEARCOAT EDGE BLENDER/ FADE OUT

Company Pro-Spray Automotive Finishes Limited
Whitehall Industrial Estate
Cambridge Road
Croxtton
St Neots
PE19 6SS
Colour@pro-spray.co.uk

Telephone +44 (0) 1480 880035 (US) 1.330.830.6000

Fax +44 (0) 1480 880108

Emergency telephone number Chemtrec 1-800-424-9300

Product code NR-6129

2. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Cyclohexanone	30-40%	108-94-1	203-631-1	R10 Xn; R20
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	30-40%	108-65-6	203-603-9	R10 Xi; R36
Xylene (Xylene, o-,m-,p-or mixed isomers)	1-10%	1330-20-7	215-535-7	R10 Xn; R20/21 Xi; R38
1,3,5-Trimethylbenzene	0-0.5%	108-67-8	203-604-4	R10 Xi; R37 N; R51/53
Cumene	0-0.5%	98-82-8	202-704-5	R10 Xn; R65 Xi; R37 N; R51/53
1,2,4-Trimethylbenzene	0.5-1%	95-63-6	202-436-9	R10 Xn; R20 Xi; R36/37/38 N; R51/53
Low boiling point naphtha - unspecified - solvent naphtha (petroleum), light arom	1-10%	64742-95-6	265-199-0	Xi; R37-66 N; R51/53 R10-67
Butylglycol acetate (2-Butoxyethyl acetate)	1-10%	112-07-2	203-933-3	Xn; R20/21

3. HAZARDS IDENTIFICATION

Main hazards May cause sensitisation by skin contact. Flammable Harmful by inhalation. Irritating to eyes. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

Skin contact May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

Inhalation May cause irritation to mucous membranes. Move the exposed person to fresh air.

Ingestion May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

Print date 24-Jun-2008

OUTRAGEOUS EXTREME CLEARCOAT EDGE BLENDER/ FADE OUT

Revision

3

Revision date

24-Jun-2008

5. FIRE FIGHTING MEASURES

Extinguishing media	Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards	Burning produces irritating, toxic and obnoxious fumes.
Protective equipment	Wear suitable respiratory equipment when necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Cyclohexanone	WEL 8-hr limit ppm: 10 WEL 15 min limit ppm: 20	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: -
2-methoxy-1-methylethyl acetate (1-Methoxypropylacetate)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 274 WEL 15 min limit mg/m3: 548
Xylene (Xylene, o-,m-,p-or mixed isomers)	WEL 8-hr limit ppm: 50 WEL 15 min limit ppm: 100	WEL 8-hr limit mg/m3: 220 WEL 15 min limit mg/m3: 441
Cumene	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50	WEL 8-hr limit mg/m3: 125 WEL 15 min limit mg/m3: 250
Butylglycol acetate (2-Butoxyethyl acetate)	WEL 8-hr limit ppm: 20 WEL 15 min limit ppm: 50	WEL 8-hr limit mg/m3: - WEL 15 min limit mg/m3: -

Engineering measures	Ensure adequate ventilation of the working area.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	In case of splashing, wear: Approved safety goggles.
Protective equipment	Wear protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description	Liquid.
Flash point	23~<32°C
Water solubility	insoluble in water.
VOC (Volatile organic compounds)	955 g/l

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions.
------------------	---------------------------------

11. TOXICOLOGICAL INFORMATION

OUTRAGEOUS EXTREME CLEARCOAT EDGE BLENDER/ FADE OUTRevision 3
Revision date 24-Jun-2008**12. ECOLOGICAL INFORMATION****13. DISPOSAL CONSIDERATIONS****General information** Dispose of in compliance with all local and national regulations.**14. TRANSPORT INFORMATION****ADR/RID**

UN 1263	Packing group III
Class 3	Hazard ID 33
Proper Shipping Name PAINT RELATED MATERIAL .	

IMDG

UN 1263	Packing group III
Class 3	Marine pollutant .
EmS Code F-E S-E	

IATA

UN 1263	Packing group III
Class 3	Subsidiary risk -
Packing Instruction (Cargo) 310	Maximum quantity 220 L
Packing Instruction (Passenger) 309	Maximum quantity 60 L

Further information The product is not classified as dangerous for carriage.**15. REGULATORY INFORMATION****Symbols** Xn - Harmful**Risk phrases**

R43 - May cause sensitisation by skin contact.
 R10 - Flammable.
 R20 - Harmful by inhalation.
 R36 - Irritating to eyes.
 R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

OUTRAGEOUS EXTREME CLEARCOAT EDGE BLENDER/ FADE OUT

Revision 3
Revision date 24-Jun-2008

16. OTHER INFORMATION

Text of risk phrases in Section 2	<p>R10 - Flammable. R20 - Harmful by inhalation. R20/21 - Harmful by inhalation and in contact with skin. R36 - Irritating to eyes. R36/37/38 - Irritating to eyes, respiratory system and skin. R37 - Irritating to respiratory system. R38 - Irritating to skin. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 - Harmful: may cause lung damage if swallowed. R66 - Repeated exposure may cause skin dryness or cracking. R67 - Vapours may cause drowsiness and dizziness.</p>
Further information	<p>The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.</p>
Revision	<p>This document differs from the previous version in the following areas: 9 - flash point.</p>
Maximum content of VOC	<p>955 g/l</p>