

OUTRAGEOUS®

TECH DATA SHEET

NR-6128 Basecoat Blender

Form: OCF15 Rev. 11/30/05

DESCRIPTION:

Outrageous® NR-6128 Basecoat Blender is designed to make fading and blending basecoats easy. Basecoat Blender can also be used as an inter-coat clear for taping and artwork.



SUBSTRATES:

Through-cured sanded paintwork, sanded 2 component primer filler / surfacer and Outrageous basecoats / effects.



MIXING:

No mixing. Ready to use.

POT LIFE:

n/a

APPLICATION:

TOUCH UP AND BLENDS:

1. Prepare panels as usual. Sand adjacent non-primed areas and panels with P1200 and an ultra fine scuff pad.
2. Clean entire area with AR-6120 Outrageous Pre-Wipe or AR-6121 Outrageous Compliant Pre-Wipe.
3. Apply one coat of Outrageous NR-6128 Basecoat Blender to the entire area.
4. Apply basecoat, according to directions, to the repaired area until full opacity has been achieved.
5. Mix Outrageous NR-6128 Basecoat Blender with Outrageous Colour at a 1:1 mix ratio and fade out the surrounding areas with reduced air pressure (1.5 bar).
6. Finish by coating the entire area with Outrageous Clearcoat.

PROTECTIVE CLEAR:

1. Apply 1 or 2 coats of Outrageous NR-6128 Basecoat Blender after the last coat of basecoat colour has flashed.
2. Allow 1 hour before taping (tape time will vary with weather and shop conditions).
 - a. Note: Outrageous NR-6128 Basecoat Blender will dry to a semi-gloss feel that is dry to the touch.
 - b. Note: If Outrageous NR-6128 Basecoat Blender dries for more than 1 hour, lightly wet sand with 500 or 600 grit abrasive to ensure proper topcoat adhesion.
3. Do artwork with a minimum of tape contact and remove quickly for topcoats.
4. Paint entire area with Outrageous Clearcoat.

SPECIAL NOTES:

NOTE: Dispose of in accordance to state, local and federal regulations.



HEALTH & SAFETY:

Read all warnings, first aid and safety for all components before using. Keep out of reach of children and animals. Wear a properly fitting NIOSH/MSHA approved respirator. Select positive pressure supplied respirator (TC-19C or equivalent) for isocyanates. Follow the respirator manufacturer's directions for use. Protect hands with impervious rubber gloves. Wear face, skin and eye protection. Outrageous® Custom Finishes' products are for industrial use by professional, trained painters.



CONTACT:

Outrageous Custom Finishes

The Trade Group Refinish House,

Gelders Hall Industrial Estate,

Shepshed, Leicestershire LE12 9NH

Tel: 01509 651122 Fax: 01509 651166

Email: sales@outrageousfinishes.co.uk www.outrageousfinishes.co.uk