

OUTRAGEOUS®

TECH DATA SHEET

Clearcoat Edge Blender/Fade Out NR-6129

JUNE 2008

DESCRIPTION:

Outrageous®NR-6129 Clearcoat Edge Blender/Fade Out was developed for use with all paint systems. It is specially formulated for dissolving the overspray and fading out the edge created during spot repairs or blending to make fading and blending clearcoats easy.

Use NR-6129 Clearcoat Edge Blender; Eliminate dry, patchy edges and visible repairs.

R6029 Clear Edge Blender can be added to 2K Clearcoats for undetectable touch-ups and blends. In short, it gives you outstanding results and high customer satisfaction.



SUBSTRATES:

Invisible repairs easily achieved.
Can be used with all 2 Component Clearcoat



MIXING:

Mix 5 parts NR-6129 Clear Edge Blender to 1 part Activated 2 Component Clearcoat.

APPLICATION:

Apply 1 coat over the overspray edge, fading out into the still intact existing finish.
Allow 2 – 5 minutes flash time (70°F/20°C) after completing the fade out.

SPECIAL NOTES:

NOTE: Dispose of in accordance to state, local and federal regulations.



HEALTH & SAFETY:

Read all warnings, first aid and safety for all components before using. Keep out of reach of children and animals. Wear a properly fitting NIOSH/MSHA approved respirator. Select positive pressure supplied respirator (TC-19C or equivalent) for isocyanates. Follow the respirator manufacturer's directions for use. Protect hands with impervious rubber gloves. Wear face, skin and eye protection. Outrageous® Custom Finishes' products are for industrial use by professional, trained painters.



CONTACT:

Outrageous Custom Finishes
The Trade Group Refinish House,
Gelders Hall Industrial Estate,
Shepshed, Leicestershire LE12 9NH
Tel: 01509 651122 Fax: 01509 651166
Email: sales@outrageousfinishes.co.uk www.outrageousfinishes.co.uk